

X

24759
S/119/61/000/007/001/008
D247/D306

Measurement of liquid flow...

For sufficiently low values of Z the amplitude is independent of T_{1e} . Sensitivity of the flowmeter can be increased at the expense of range of measurement. In addition, a correction for temperature effects is necessary. The simplest method of measurement of velocity of flow in a pipe consists of the measurement of time required for the molecules of liquid to traverse a known length of pipe. The use of this method excludes the need for calibration and permits the measurement of velocity of flow of one of the phases in a polyphase liquid. This method can be applied to the measurements of velocity of gaseous-liquid mixtures. The liquid flow measurement can be based on so-called "apparatus effect" which takes place if a flow transmitter has a form of a circular path. The nuclear resonance occurs at a frequency of oscillating field differing from the frequency of nuclear precession by E,

$$\Delta\omega = \frac{w}{2\pi d} \times$$

cycles

$$\times \ln \frac{S_{max}}{S_{min}}$$

(seln)

Card 4/5

24759

Measurement of liquid flow...

S/119/61/000/007/001/008
D247/D306

where S_{\max} and S_{\min} - maximum and minimum radii of nuclear path in the transmitter; d - pipe diameter; w - velocity of liquid flow, assumed uniform throughout the cross section. In this way, if the frequency difference is measured at which a signal of ($S = \infty$) and on a rectilinear section of pipe netic field, the velocity of flow becomes F .

$$w = \frac{2\pi f d}{\ln \frac{S_{\max}}{S_{\min}}}.$$

Transmitters having yet different shape and construction can be used with success. The method is covered by the author's certificate No. 125906 and No. 131517. There are 4 figures and 4 Soviet-bloc references. X

Card 5/5

S/170/61/004/005/009/015
B111/B214

AUTHOR: Zhernovoy, A. I.

TITLE: A new method for the investigation of the longitudinal turbulent diffusion in a pipe line

PERIODICAL: Inzhenerno-fizicheskiy zhurnal, v. 4, no. 5, 1961, 91-93

TEXT: The direct method for the investigation of molecular diffusion through a cross section consists in labelling the molecule on one side of the cross section and following its appearance on the other side in a certain time. This can be done by the use of tracer atoms. The difficulty consists in having a sharp boundary between the labelled and the unlabelled liquid. An investigation of the nutation effect showed that with its help a sharp boundary could be obtained separating the polarized and the unpolarized liquid. For this purpose, use is made of an arrangement shown in Fig. 1. If no resonance with the oscillating field appears in the coil 2, the nuclear resonance signal can be determined at the detector. If, however, a resonance is

$$T = \frac{6}{\gamma \Delta H_1}$$

Card 1/3

A new method ...

8/170/61/004/005/009/015
B111/B214

where ΔH_1 is the inhomogeneity of the external magnetic field perpendicular to the liquid current, and γ is a constant. By means of the nuclear resonance method, one part of the liquid can be polarized while the other cannot be polarized. The length of the unpolarized liquid in the first moment is equal to $W_{\text{mean}} \cdot T$ (W_{mean} = mean velocity of the molecule). At the instant at which the first layer of separation enters the coil 4 the nuclear resonance signal decreases; at the instant at which the second layer leaves coil 2 the decrease of the signal amplitude ceases. It is thus possible to record the layer of separation accurately. If the time interval Δt in which the amplitude of the signal completely vanishes is known, the length of the diffusion boundary can be determined. In this case, the diffusion coefficient is given by the formula:

$$D_t = \frac{l_d^2 W_{\text{mean}}}{81 \cdot l_o \ln \frac{1}{e} \cdot \frac{6W_{\text{mean}}}{l_d \gamma \Delta H_1}}, \text{ where } l_o \text{ is the length of the pipe}$$

line. Three experiments were performed: 1) $W_{\text{mean}} = 427 \text{ cm/sec}$, $l_d = 12 \text{ cm}$,

Card 2/3

A new method ...

8/170/61/004/005/009/015
B111/B214

$H' = 0.1 \text{ A oe/ohm}$, $D_t = 21 \text{ cm}^2/\text{sec}$; 2) $\Delta t = 0.12 \text{ sec}$, $l_o = 114.5 \text{ cm}$,
 $l_d = 11.4 \text{ cm}$, $l_a = 15 \text{ cm}$ (l_a - length of the absorption coil);
 $W_{\text{mean}} = 219 \text{ cm/sec}$, $D_t = 6 \text{ cm}^2/\text{sec}$; 3) $\Delta t = 0.08 \text{ sec}$, $l_o = 10 \text{ cm}$,
 $l_d = 2.5 \text{ cm}$, $l_a = 15 \text{ cm}$, $W_{\text{mean}} = 219 \text{ cm/sec}$, $D_t = 4.7 \text{ cm}^2/\text{sec}$. There are
1 figure and 2 Soviet-bloc references.


ASSOCIATION: Institut inzhenerov zheleznochaynogo transporta im. akad.
V. N. Obraztsova, Leningrad (Institute of Railway Transport
Engineering imeni Academician V. N. Obraztsov, Leningrad)

SUBMITTED: October 21, 1960

Legend to Fig. 1: Block scheme:

- 1) Strong magnet for polarization,
- 2) coil for the production of nutation,
- 3) magnet for the production of a homogeneous magnetic field,
- 4) coil for the pick-up of the nuclear resonance,
- 5) nuclear resonance detector,
- 6) r-f generator.

Card 3/3.



ZHERNOVAY, A.I.

Absolute method for determining the sign of gyromagnetic ratio
in experimenting with a flow transducer. Prib.i tekhn.eksp. 6
no.5:182-183 S-0 '61. (MIRA 14:10)

1. Leningradskiy institut inzhenerov zheleznodorozhnogo transporta.
(Nuclear magnetic resonance and relaxation)

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

ZHERNOVoy, A.I.; ARKHANGEL'SKIY, A.A.; LATYSHEV, G.D., akademik

Using nuclear resonance in magnetic flaw detection. Vest.AN Kazakh.
SSR 17 no.3:105-107 Mr '61. (MIRA 14:3)

1. Akademiya nauk KazSSR.
(Metals—Defects) (Nuclear magnetic resonance)

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

9.2574
AUTHORS:

Zhernovoy, A.I. and Latyshev, G.D.
39308
S/707/62/005/000/009/014
D290/D308

TITLE:

The relation between the frequency of a nuclear resonance maser and the parameters of the apparatus

SOURCE:

Akademiya nauk Kazakhskoy SSR. Institut yadernoy fiziki. Trudy, v. 5. Alma-Ata, 1962. Fizika chastits vysokikh energiy. Struktura yadra, 112-116

TEXT:

The authors studied a system consisting of a tuned circuit linked with a coil containing a specimen that is in a magnetic field of H oersted; they found a relation between the resonant frequency of the circuit, ω_0 , and the frequency of the nuclei in the specimen in a magnetic field of H oersted, and the relaxation frequency of the signal induced in the specimen. The authors assumed that the effect of the nuclei of the polarized nuclei on the circuit was equivalent to a complex magnetic susceptibility of the nuclei and the impedance of the circuit

Card 1/2

18.8300 1454

33473

S/170/62/005/002/005/009
B104/B138

AUTHOR: Zhernovoy, A. I.

TITLE: Measurement of large relaxation times in a continuous stream
of liquid

PERIODICAL: Inzhenerno-fizicheskiy zhurnal, v. 5, no. 2, 1962, 64 - 71

TEXT: A stream of liquid flows through a pipe, first through a powerful polarizing field and then through a section with a pickup at its end. The liquid is polarized with a shielded magnet having a volume of 400 cm³ between the pole pieces. The field strength is 10,000 oe. Relaxation times ranging from 0.3 to 6 sec were measured by two methods. In the first, the length of the pipe was continuously varied between the polarizing field and the pickup. In the second, calibrated pieces were inserted between the polarizing field and the pickup. The optimum volume of polarized liquid, the ranges of measurement, and the least error were determined. This arrangement was used to test the corrosion of a metal. The relaxation time was determined for a 0.15% solution of HCl in water, into which pieces of iron coated with poor quality acid-resistant varnish had been

Card 1/2

33473

S/170/62/005/002/005/009

B104/B138

Measurement of large ...

immersed. The relaxation time was shortened by the occurrence of iron ions in the water. The ion concentration was measured with a calibration curve plotted from the relaxation times of water with different FeCl_3 concentrations. There are 3 figures and 31 references: 6 Soviet and 25 non-Soviet. The four most recent references to English-language publications read as follows: Solomon I. J., Phys. Rad., 20, no. 8, 788, 1959; Das T. P., Saha A. K., Phys. Rev., 93, 749, 1954; Hahn E. L., Phys. Rev., 6, no. 11, 4, 1953; Chiarotti G., Guilotto L., Phys. Rev., 93, no. 6, 1241, 1954.

ASSOCIATION: Institut inzhenerov zheleznodorozhnogo transporta, g. Leningrad (Institute of Engineers of Railroad Transportation, Leningrad)

SUBMITTED: June 8, 1961

Card 2/2

36865
S/170/62/005/005/015/015
B104/B102

5.1175

AUTHOR: Zhernovoy, A. I.

TITLE: A new method of measuring the flow rate of liquids by using nuclear magnetic resonance

PERIODICAL: Inzhenerno-fizicheskiy zhurnal, v. 5, no. 5, 1962, 112 - 115

TEXT: By means of a solution of Bloch's equation the vector of nuclear magnetization of the liquid in the volume V_A (Fig. 1) is given by

$$M = \chi_0 H_n \left[1 - \exp \left(-\frac{V_n}{qT_1} \right) \right] \exp \left(-\frac{V_n}{qT_1} \right) \times \quad (4). \\ \times \exp \left[-\frac{V_n}{q} \left(\frac{1}{T_1} + \frac{1}{T_2} \right) \right] \cos \gamma H_1 \frac{V_n}{2q}.$$

With increasing magnetic field intensity H_1 of coil 1 the signal intensity disappears periodically. The values of H_1 at which the signal

Card 1/2

S/170/62/005/005/015/015
B104/B102

A new method of measuring the ...

intensity becomes zero are connected with the flow rate of the liquid:
 $H_{10} = q(2n-1)\pi/\gamma V_H$ (5). Knowing the a-c field intensity in the coil 1 at which the nuclear resonance signal disappears one can determine the flow rate q of the liquid. The error in measuring q is:
 $\Delta q/q = 2/a(2n-1)\pi$. The method allows a continuous recording of the absolute value and has a small inertia; it needs no highly homogeneous magnetic field and no toroidal tube. There is 1 figure.

SUBMITTED: December 11, 1961

Fig. 1. Setup of a flow rate measurement. Legend: (1), (2) rf coils; (3) rf generator; (4) nuclear magnetic resonance detector; (H_n) magnetic field intensity; (V_n), (V_H) and (V_A) tube volumes.

Card 2/3

GO

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

1 2 3 4 5 6 7 8 9

SW

1 2 3 4 5 6 7 8 9

1 2 3 4 5 6 7 8 9

1 2 3 4 5 6 7 8 9

TOPIC TAGS: nuclear magnetic resonance

Card 1/2

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

L 17864-67
ACCESSION NR AP3003701

to be given to associations that have been
prime with a given source or reference.

ASSOCIATION: none

SUBMITTED: OO

DATE ACQ: 02Aug63

ENCL: CO

SUB CODE: SD, PH

NO REF SOV: 000

OTTER: 000

Card 2/2

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

ASSISTANT IN THE FIELD OF INFORMATION

Card 1/2

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

CONFIDENTIAL
EXCLUDED FROM AUTOMATIC
DECLASSIFICATION

THIS DOCUMENT IS PREPARED IN ACCORDANCE WITH
THE AUTOMATIC DECLASSIFICATION SCHEDULE.
RELATING INFORMATION IS LOCATED AS FOLLOWS:

DISSEMINATION: none

SUBMITTED: 00 DATE: 11-11-1986 BY: 00

SUB CODE: SD, PH NO REP Sov: 000 DTG: 000

Card 2/2

TOP SECRET//NOFORN//EYES ONLY

TOP SECRET//NOFORN//EYES ONLY
TOP SECRET//NOFORN//EYES ONLY

QUESTION: The main function of the filter system is to remove

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

Card 2 of 1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

ZHERNOV, Aleksandr Ivanovich; LATYSHEV, Georgiy Dmitriyevich;
MEL'NIKOVA, A.I., red.

[Nuclear magnetic resonance in a flowing liquid] IAdernyi
magnitnyi rezonans v protokhnoi zhidkosti. Moskva, Atom-
izdat, 1964. 252 p.
(MIRA 17:6)

ZHERNOVY, A.I.; RUKHIN, A.B.

Setup for measuring the spin-lattice relaxation time in nuclei
of a liquid in contact with a powder. Izv. AN Kazakh. SSR.
Ser. fiz.-mat.nauk no. 2:63-69 '63. (MIRA 17:6)

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

L 8621-66 EMT(U) IIP(a) MM/00
ACC NR: AP5027039

SOURCE CODE UR/0120/65/000/005/0230/0221

AUTHOR: Zhernovoy, A. I.; Stakhov, O. V.; Fedorov, N. D.

ORG: Institute of Nuclear Physics, AN KazSSR, Alma-Ata (Institut yadernoy fiziki AN
KazSSR) 44, 55

TITLE: The measurement of strong magnetic fields by means of an NMR flow sensor

SOURCE: Pribory i tekhnika eksperimenta, no. 5, 1965, 220-221

TOPIC TAGS: NMR, strong magnetic field, magnetic field measurement, flow research,
electromagnet 21, 411, 55

ABSTRACT: NMR detectors with fixed probes are often used for the recording and stabilization of strong magnetic fields. However, in addition to the need for various exchangeable sensors, it is often necessary to either place a part of the electronic circuitry into the magnetic gap or increase the length of the HF cable. Since both approaches are far from satisfactory, the authors introduce a flow of liquid which is subsequently used for the NMR measurement of the field of a ø 1.5 m pole piece electromagnet. The measurements are based on the nutation method applied to the nuclei of the liquid; these nuclei are polarized within the magnetic field under investigation, while the recording of the resonance is carried out by the NMR sensor located outside the field under study within an auxiliary field of a permanent magnet. The article presents a description of the device and outlines the characteristics of the strong magnetic field measurements. The minimum value of the recorded field

Card 1/2 UDC: 539.283.078

L 8621-66

ACC NR: AP5027039

5

(limited basically by the signal-to-noise ratio at the exit of the NMR indicator) is in the 300 - 500 Oe region, the maximum (depending on the HF power supply circuit) can be extended above 25 kOe ($f > 100$ Mc) provided powerful generators or specially matched coll. HF generator pairs are used. The theoretical recording accuracy does not exceed $\pm 10^{-5}$, in practice, it was no better than $5 \cdot 10^{-5}$ since the frequency tuning of the CH-1A generator did not allow sufficiently accurate frequency adjustments. Authors thank A. A. Skaxoduh for his help.

Orig. art. has: 1 formula and 1 figure.

1/12

SUB CODE: NP,EM / SUBM DATE: 27Jun64 / ORIG REF: 001

Jrn

Card 2/2

ZHERNOVY, A.I.; STAKHOV, O.V.; FEDOROV, N.D.

Measurement of strong magnetic fields by means of a flow
transducer of nuclear magnetic resonance. Prib. i tekhn.eksp.
10 no.5:220-221 S-O '65.

1. Institut yadernoy fiziki AN Kazakhskoy SSR, Alma-Ata.
(MIRA 19:1)
Submitted June 27, 1964.

ZHERNOVoy, A.I., kand.fiziko-matemat.nauk

Self-exciting device with a flow-through transmitter of nuclear
resonance. Vest. AN Kazakh.SSR 20 no.11:72-73 N '64.

(MIRA 18:2)

YEKATERININ, V.V.; ZHERNOVY, A.I.; STAKHOV, O.V.

The IAMR pulse-frequency flowmeter. Izm. tekhn. no.3:54-56 Mr '65.
(MIRA 18:5)

ZHERNOVoy, A.I.; STASEVICH, V.M.

Flowmeter based on the principle of nuclear magnetic resonance.
Izv. vys. ucheb. zav.; prib. 8 no.2:45-48 '65.

(MIRA 18:5)

1. Institut yadernoy fiziki AN Kazakhskoy SSR.

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

ZHERNOVY, A.I.; POLYAKOV, A.I.; YAKOVLEV, G.I.

Effect of nuclear nutation in inhomogeneous magnetic fields.
Izv. AN SSSR Ser. fiz. 29 no.2:304-305 F '65.

(MIRA 18:3)

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

ZHERNOVY, A.I.; POLYAKOV, A.I.; YAKOVLEV, G.I.

Width of the nuclear magnetic resonance line in a flow transducer.
Izv. AN SSSR Ser. fiz. 29 no.2:311-312 F '65.

Nonresonance mutation of nuclei in nuclear magnetic resonance.
(NIMA 18;3)
Ibid.:313-314

ZHERNOV, A.I. & PIVOVAROV, S.P.

Direct method for large T_1 time measurements in a moving liquid.
Prib. i tekhn. eksp. 9 no.4:104-106 Jl-Ag '64. (MIRA 17:12)

1. Institut yadernoy fiziki AN KazSSR.

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

LATYSHEV, G.D., akademik; ZHERNOVOY, A. I., kand. fiziko-matemat. nauk

Nonresonance methods for the demagnetization and magnetic reversal
of nuclei in a flowing liquid. Vest. AN Kazakh. SSR, 19 no.8:
32-35 Ag '63. (MIRA 17:7)

YEKATERININ, V.V.; ZHERNOVY, A.I.; YAKOVLEV, G.I.

Nuclear magnetic resonance spectrometer in a weak field.
Izv. AN Kazakh. SSR. Ser. fiz.-mat. nauk no. 2:58-62 '63.
(MIRA 17:6)

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

PIVOVAROV, S.P.; RYABIKIN, Yu.A.; ZHERNOVYY, A.I.; LATYSHEV, G.D.

Apparatus for the stabilization of inhomogeneous magnetic fields
based on the electron paramagnetic resonance method. Izv. AN SSSR
Ser. fiz. 29 no.1:166-167 Ja '65. (MIRA 18:2)

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

YEKATERININ, V.V.; ZHERNOVY, A.I.; SHEVELENKO, V.D.

Magnetic field stabilizer operating on the basis of a spin generator.
Izv. AN SSSR Ser. fiz. 29 no.1:168-171 Ja '65.

(MIRA 18:2)

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

ZHERNOVY, A.I.; YAKOVLEV, G.I.

Observation of negative hydration by the method of nuclear magnetic resonance. Zhur.strukt.khim. 4 no.6:914 N-D '63. (MIRA 17:4)

1. Institut yadernoy fiziki AN KazSSR.

SAPOZHENKOV, Yu.F.; GORELOV, Yu.K.; ZHERNOVOY, I.V.; SVYATOY, V.I.

Distribution and ecology of the ratel (*Mellivora capensis indica* Kerr.) in Turkmenistan. Zool. zhur. 42 no.6:961-964 '63. (MIRA 16:7)

1. The State University of Moscow, Turkmenian Anti-Plague Station, Ashkhabad and Game Preserve of Badkhyz.
(Turkmenistan--Ratel)

SEROGANTSEV, V.T.; ARTEMOV, V.A.; ZHERNOVOY, M.N.; MOROTSKIY, L.P.

Using the pipes of a gas pipeline as a remote-control channel.
Gaz.delo no.1:14-16 '64. (MIRA 17:4)

1. Vsesoyuznyy nauchno-issledovatel'skiy institut prirodnogo gaza i
Minskoye upravleniye magistral'nykh gazoprovodov.

ZHERNOVY, N., nauchnyy sotrudnik

Over-all mechanization of haymaking. Nauka i pered. op v
sel'khoz. 9 no.6:25 Je '59. (MIRA 12:9)

1.Kalininskaya gosudarstvennaya sel'skokhozyaystvennaya optytnaya
stantsiya.
(Hay--Harvesting)

"APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1

APPROVED FOR RELEASE: 03/15/2001 CIA-RDP86-00513R002064720009-1"

TERENT'YEV, A.P.; SYAVTSILIO, S.V.; SAVUSHKINA, V.I.; ZHERNOVSKAYA, Ye.M.;
CHARSKAYA, B.A.

Synthesis of 2-ethylanthraquinone, labelled by C¹⁴ carbon in the
nucleus. Dokl.AN SSSR 107 no.3:417-419 Mr '56. (MIRA 9:7)

1. Chlen-korrespondent AN SSSR (fer Terent'yev).
(Anthraquinone) (Carbon--Isotopes)

KULIKOV, V.O.; BORNATSKIY, I.I.; ZARUBIN, N.G.; DOROFEEV, G.A.;
KALUZHISKIY, Ye.A.; KAZAKOV, A.A.; KOVAL', R.P.; KORNEVA, N.K.;
TRET'YAKOV, Ye.V.; TRUNOV, Ye.A.; Prinimali uchastiye: ANDREYEV, V.L.;
GORDIYENKO, V.V.; GRINEVICH, I.P.; GUBAR', V.F.; DOLINENKO, V.I.;
ZHERNOVSKII, V.S.; ZHIGALOVA, Z.I.; KOMOV, N.G.; KURAPIN, B.S.;
OLESHKEVICH, T.I.; PRIKHOZHENKO, Ye.

Mastering the operations of 650- and 900-ton (mega - gram) capacity
open-hearth furnaces at the Il'ich metallurgical plant. Stal' 25
no.8:805-807 S '65. (MIRA 18:9)

1. DONNIICHERMET i Zhdanovskiy metallurgicheskiy zavod imeni Il'icha.

YAKOVLEV, Yu.N., kand. tekhn. nauk; PANIOTOV, Yu.S.; THERKULSKIY, V.S.;
BELYAYEV, Yu.P.

Slag formation and smelting in 650 and 900-ton capacity
open-hearth furnaces. Met. i gornorud. prom. no.6:24
N-D '64.

(MIRA 18:3)

ZHERO, O.G.

Basic characteristics of the tectonics and oil potential of the base-
ment in the northern part of the Turgay trough. Trudy SNIIGGIMS no.27:
25-34 '62. (MIRA 16:9)

1. Sibirskiy nauchno-issledovatel'skiy institut geologii, geofiziki
i mineral'nogo syr'ya.

(Turgay Gates--Geology, Structural)
(Turgay Gates--Petroleum geology)

4.

ZHERO, O.G.

Reservoir properties of sandstones in Upper Paleozoic
sediments of the Kuznetsk Basin. Trudy SNIIGGIMS
no.17:113-122 '61. (MIRA 15:9)
(Kuznetsk Basin—Oil sands)

RUBANIK, V.G.; KORMEYCHIK, Zh.N.; MEL'NIK, A.F.; SOLONINOVA, I.N.;
ZHERONKINA, T.A.; KALUGIN, E.S.; TKACHENKO, V.S.; BESSCHETNOV,
P.P.; PROTASOV, A.N.; PARAVYAN, A.V., doktor biol. nauk, ctv.
red.

[List of trees and shrubs recommended for landscaping in
populated places of Kazakhstan] Spisok derev'ev i kustarnikov,
rekomeneduyemykh dlia ozelenenija naselenijkh punktov Kazakhstana.
Alma-Ata, Izd-vo AN KazSSR, 1963. 85 p.

(MIRA 17:3)

1. Akademija nauk Kazakhskoy SSR. Institut botaniki. 2. Glavnoye upravleniya lesnogo khozyaystva i okhrany lesa Soveta
Ministrov Kazakhskoy SSR (for Tkachenko). 3. Kazakhskiy
sel'skokhozyaystvennyy institut (for Besschetnov, Protasov).

RUBANIK, V.G.; ZHERONKINA, T.A.

Grafting Siberian pine on Scotch pine in the Alma-Ata Botanical Garden. Trudy Alma-At. bot. sada 7:76-85 '63. (MIRA 16:10)

RUBANIK, V.G., kand. biolog. nauk; ZHERONKINA, T.A.

Some data on the grafting of conifers. Vest. AN Kazakh.
SSR 18 no.10:90-93 O '62. (MIRA 17:9)

ZHERTVIN, Nikita Petrovich; TUNKOV, Vladimir Pavlovich; PERTSEV,
Mikhail Andreyevich; PAISOV, Aleksey Ivanovich; PCDVOYSKIY,
Lev Nikolayevich; KAZARNOVSKIY, L.Sh., red.; OZERETSKAYA, A.L.,
red. izd-va; KARASEV, A.I. tekhn. red.

[Commercially pure iron]Tekhniceski chistoe zhelezo. Moskva,
Metallurgizdat, 1962. 198 p. (MIRA 16:1)
(Iron)

ABLOV, A.V.; YABLOKOV, Yu.V.; ZHERU, I.I.

Electron paramagnetic resonance studies of the structure of certain
copper acetates and copper chloroacetates. Dokl. AN SSSR 141
no.2; 343-345 N '61.

(MIRA 14:11)

1. Institut khimii Moldavskogo filiala AN SSSR i Fiziko-tehnicheskii
institut Kazanskogo filiala AN SSSR. Predstavлено akademikom A.Ye. Arbuzovym.

(Copper acetate--Spectra)

ZHERU, I.I.

Use of the method of invariants in the theory of hyperfine interaction, Ukr. fiz. zhur. 10 no.7:726-733 Jl '65.
(MIRA 18:8)

1. Institut poluprovodnikov AN UkrSSR, Kiyev.

ZHERU, M.I.

Metasomatic and retrograde-metamorphic processes in the
carbonate rocks of the "Pereval" deposit (southern Lake Baikal
Region). Trudy IGEM no.48:161-174 '61. (MIRA 15:1)
(Baikal Lake region—Rocks, Carbonate)

ZHATEV, M.I.
SIMONOV, A.I.; MELNIK, N.I., kandidat geologo-mineralog. nauk

Lithology of clayey of the Orlbozhikhi deposit in the Moldavian
S.S.R. Izv. Mold. fil. AN RSR no. 62(7-68) '61. (MIRPA 1787)

ZHERU, M.I.

Magnesite in marbles of the "Pereval" deposit. Zap. Vses. min.
ob-va 88 no.5:591-594 '59. (MIRA 13:2)
(Baikal region--Magnesite)

AUTHORS:

Syavtsillo, S. V., Savushkina, V. I.,
Zhernovskaya, Ye. M.

SOV/79-20-7-8/64

TITLE:

The Synthesis of 2-Ethylanthrone and 2-Ethyl-10-Oxanthrone
Radioactivated by C¹⁴ in the Ring, and the Investigation of
Some of Its Properties(Sintez 2-ethylanthrona i 2-ethyl-10-oksan-
trona, mechenyykh uglerodom C¹⁴ v yadre, i issledovaniye neko-
torykh ikh svoystv)

PERIODICAL:

Zhurnal obshchey khimii, 1958, Vol 28, Nr 7,
pp. 1752 - 1755 (USSR)

ABSTRACT:

The authors synthesized the 2-ethylanthrone radioactivated
by C¹⁴ in the ring by means of the reduction of the 2-ethylan-
thraquinone also radioactivated by C¹⁴ (Ref 1). The reduction
was carried out analogous to that of anthrone (Ref 2).
2-ethylanthrone was obtained in pure state (melting point 62°);
it did not contain an enol form and it did not tautomerize on
long storing in solid form and in benzene solutions. Earlier
(Ref 3) the 2-ethylanthrone was obtained only in the mixture
with 2-ethylantranol in the solution of 4-ethyl-diphenyl
methane carboxylic acid in concentrated sulfuric acid. The

Card 1/3

The Synthesis of 2-Ethylanthrone and 2-Ethyl-10-Oxanthrone Radioactivated by C¹⁴ in the Ring, and the Investigation of Some of Its Properties

SOV/79-28-7-8/64

final product melted at 67-75°. The hitherto not described 2-ethyl-10-oxanthrone (92-93°) was obtained from the 2-ethylanthrone radioactivated by C¹⁴ according to the synthesis method by Meyer (Ref 4)(Mayyer), i.e. by bromination of the 2-ethylanthrone with subsequent saponification of the obtained product with 2-ethyl-10-bromanthrone radioactivated by C¹⁴. In order to avoid the formation of oxidation products this bromination and the separation of the latter were carried out at low temperatures (-8 to -20°). Thus the radioactive 2-ethylanthrone (in a yield of 51%) radioactivated by C¹⁴ was for the first time synthetized, as well as the acetate of the ethyl anthranol and the 2-ethyl-10-oxanthrone (59%) radioactivated the same way in the ring. The hydration and oxidation of the mentioned compounds were carried out. There are 6 references, 3 of which are Soviet.

SUBMITTED: May 18, 1957
Card 2/3

The Synthesis of 2-Ethylanthrone and 2-Ethyl-10-Oxanthrone Radioactivated by C¹⁴ in the Ring, and the Investigation of Some of Its Properties SOV/79-20-7-8/64

1. Ethyl dérivatives--Synthesis 2. Ethyl derivatives--Properties 3. Ethyl dérivatives--Radioactivity 4. Carbon isotopes (Radioactive)--Applications

Card 3/3

ZHERO, O.G.

Oil and gas potentials of the Kuznetsk Basin. Trudy SNIIGIMS
no.9:76-86 '60. (MIRA 14:7)
(Kuznetsk Basin--Petroleum geology)
(Kuznetsk Basin--Gas, Natural--Ecology)

"APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1

ZHERO, V.

The Polish Scientific Institute of the Sugar Industry Aiding the Production.
Leka Promishlenost (Light Industry), #7-12:43;July-Dec 1955

APPROVED FOR RELEASE: 03/15/2001

CIA-RDP86-00513R002064720009-1"

KRUTIKOV, A.; SELISHCHEV, G.; GABIS, V.; LIBERMAN, A.; KOMNOVA, L.;
BUT, A.; SUTANKIN, A.; ZHEROMSKAYA

Unremitting attention to self-service stores! Sov.torg. 33
no.7:12-13 Jl '60.

(MIRA 13:7)

1. Direktor moskovskogo magazina samoobsluzhivaniya "Gastronom" No.65 (for Krutikov).
2. Direktor moskovskogo magazina samoobsluzhivaniya "Gastronom" No.64 (for Selishchev).
3. Direktor magazina No.65 Moskvoretskogo RPT (for Gabis).
4. Direktor moskovskoy bulochnoy No.44 (for Liberman).
5. Direktor moskovskoy bulochnoy No.367 (for Komnova).
6. Direktor moskovskogo magazina samoobsluzhivaniya "Mosgovoshch" (for But).
7. Direktor moskovskogo magazina samoobsluzhivaniya No.78 "Moamoloko" (for Sutankin).
8. Zamestitel' direktora magazina No.22 "Ogonek" Sverdlovskogo RPT (for Zheromskaya).

(Self-service stores)

ZHERSHNEV, V., podpolkovnik tekhnicheskoy sluzhby

Innovator. Voen. vest. 41 no.9:24-25 S '61. (MIRA 15:1)
(Shooting, Military--Equipment and supplies)

ZHERTOVSKIY, A.N., elektromekhanik; KONURIN, I.M., starshiy elektromekhanik; VOROB'YEV, A.N.; GORODETSKIY, N.P., elektromekhanik

Efficiency experts suggest. Avtom., telem. i sviaz' 4
no.1:32-33 Ja '60. (MIRA 13:4)

1. Kremenchugskaya distantsiya signalizatsii i svyazi Yuzhnay dorogi (for Zhertovskiy). 2. Yaroslavskaya distantsiya signalizatsii i svyazi Severnoy dorogi (for Konurin). 3. Starshiy inzhener Moskovsko-Okruzhnoy distantsii signalizatsii i svyazi Moskovskoy dorogi (for Vorob'yev). 4. Krasnoarmeyskaya distantsiya signalizatsii i svyazi Donetskoy dorogi (for Gorodetskiy).
(Railroads—Electronic equipment) (Radio—Repair)

ZHERU, M. I., Candidate Geolog-Mineralog Sci (diss) -- "Mineralogical-petro-graphic characteristics and genesis of the rock of the 'Pereval' deposit (southern Baykalia)". Moscow, 1959, published by the Acad Sci USSR. 21 pp (Acad Sci USSR, Inst of Geology of Ore Deposits, Petrography, Mineralogy, and Geochem of the Acad Sci USSR), 175 copies (KL, No 25, 1959, 129)

ZHERU, M.I.

Red spinel in the Pereval marbles and its secondary transformations.
Izv. AN SSSR Ser. geol. 24 no.2:107-114 F 159.

(MIRA 12:3)

I. Institut geologii rudnykh mestorozhdeniy, petrografii,
mineralogii i geokhimii AN SSSR, Moskva.
(Slyudyanka District-Spinel)

AUTHOR:

Zheru, M.I.

SOV/11-59-2-8/14

TITLE:

The Ruby Spinel in the Marbles of the Pereval Deposit and
its Secondary Transformations (Krasnaya shpinel' v
mramorakh mestorozhdeniya Pereval i yey# vtorichnyye
izmeneniya)

PERIODICAL:

Izvestiya Akademii nauk SSSR, Seriya geologicheskaya, 1959,
Nr 2, pp 107-114 (USSR)

ABSTRACT:

The ruby spinel was found in the forsterite and dolomite-calcite marbles of the Pereval deposit near the town of Slyudyanka (Irkutsk Oblast'). Almost all the marbles of the deposit underwent a series of postmagmatic transformations. The author describes in detail four types of such retrograde metamorphosis of the ruby spinel: the diopsidization, the phlogopitization, the carbonatization and the chloritization. He mentions the following geologists who worked in the region: B.Z. Kolenko, N. Voskoboinikova, D.S. Korzhinskiy, L.M. Lebedev, N.G. Sumin, P.V. Katinin and M.G. Zamuruyeva.. There are 6 photos, 1 table, and 10 references, 9 of which are Soviet and 1 German.

Card 1/2

The Ruby Spinel in the Marbles of the Pereval Deposit and its Secondary Transformations SOV/11-59-2-8/14

ASSOCIATION: Institut geologii rudnykh mestorozhdeniy, petrografii,
mineralogii i geokhimii AN SSSR (The Institute of
Geology of Mineral Deposit, Petrography, Mineralogy and
Geochemistry of the AS of the USSR) Moscow

SUBMITTED: May 27, 1958

Card 2/2

ZHERU, M.I.

Talc in rocks of the Pereval deposit and its place in retrograde
metamorphism of the Archean formation in the Lake Baikal region.
Trudy IGEM no.63:130-142 '61. (MIRA 14:9)
(Baikal Lake region--Talc)

ZHERVE, G. K.

The testing of repaired asynchronous motors. Moskva, 1948. 137 p.
(49-51220)

TK2785.25

ZHERVE, G. K.

Industrial testing of electric machinery. Leningrad, Gos. energ. izd-vo, 1950.
352 p. (51-34500)

TK401.25

ZHERVE, G. E.

Technology

Calculation for rewinding the asynchronous motor. Leningrad, Gos. energ. izd-vo, 1951.

Monthly List of Russian Accessions, Library of Congress, April 1952. UNCLASSIFIED.

ZHERVE, G. K.

Leningrad, Gos. energ. izd-vo Leningradskoe otd-nie. 1951. 142 p. (54-35083)

TK2785.255

1915.2,

(Computation of a direct current machine during rewinding) Leningrad,
Gos. energ. izd-vo, 1952. 159 p. (54-18911)

TK2474.Z5

ZHERVF, Georgiy K.

ZHERVF, Georgiy Konstantinovich; RIVLIN, L.B., redaktor; ZABRODINA,
A.A., tekhnicheskyy redaktor.

[Testing of electric machinery and transformers; manual for
workers in rural electrification] Ispytanie elektricheskikh
mashin i transformatorov; rukovodstvo dlja rabotnikov sel'-
skokhoziaistvennoi elektrifikatsii. Moskva, Gos.energ. izd-vo
1955. 199 p. (MLRA 8:12)

(Electric machinery--Testing)

ZHERVE, Georgiy Konstantinovich; RIVLIN, L.B., redaktor; ZABRODINA, A.A.,
tekhnicheskiy redaktor.

[Electrician's manual for testing electric machines] Rukovodstvo
dlia elektromonterov po ispytaniyu elektricheskikh mashin.
Moskva, Gos.energ.izd-vo, 1955. 283 p. (MLRA 8:12)
(Electric machinery--Testing)

ZHERVE, Georgiy Konstantinovich; RIVLIN, L.B., redaktor; ZABRODINA, A.A.,
tekhnicheskij redaktor

[Calculating the rewinding of asynchronous motors] Raschet asin-
khronnogo dvigatelya pri peremotke. Izd. 2-ee. Moskva, Gos. energ.
izd-vo 1956. 151 p.
(Electric motors, Induction)

VORONETSKIY, V.V., kand. tekhn. nauk; ZHERVE, G.K., inzh.

New standard: Electric machines; general technical requirements.
Vest. elektrprom. 27 no.8:67-71 Ag '56. (MLRA 10:9)

1. Nauchno-issledovatel'skiy institut Ministerstva elektrotekhnicheskoy promyshlennosti (Voronetskiy). 2. Zavod "Elektromash" imeni S.M. Kirova (for Zherve).
(Electric machinery)

PHASE I BOOK EXPLOITATION SOV/3637

Zherve, Georgiy Konstantinovich

Promyshlennyye ispytaniya elektricheskikh mashin (Industrial Testing of Electrical Machines) 2d ed., rev. Moscow, Gosenergoizdat, 1959. 504 p. 22,000 copies printed.

Ed.: L.B. Rivlin; Tech. Ed.: Ye.M. Soboleva.

PURPOSE: This book is intended for the technical personnel of electric machine-building plants, electric power stations, and other electric enterprises using electrical machines.

COVERAGE: The book deals with problems of industrial testing of electrical machines in conformance with operative standards.

Tests common for machines of all types, as well as tests applied to each particular type of machine, are described. Since testing conditions may vary in different plants, the author submits two or more methods for each test, leaving the selection of the most suitable method to the personnel concerned. The author thanks Doctor of Technical Sciences R.A. Lyuter and Engineer L.B. Rivlin. There are no references.

Card 1/14

ZHERVE, Georgiy Konstantinovich; BERGMAN, P.Ya., red.; ZHITNIKOVA, O.S.,
tekhn.red.

[Calculation of the stator winding of an asynchronous motor]

Kak rasschitat' obmotku statora asinkhronnogo dvigatelya.

Moskva, Gos.energ.iзд-во, 1960. 61 p. (Bibliotekn elektro-
montera, no.26).

(MIRA 14:1)

(Electric motors, Induction--Windings)

DOMBROVSKIY, Vyacheslav Vyacheslavovich; YEREMEYEV, Aleksandr
Sergeevich; IVANOV, Nikolay Pavlovich; IPATOV, Pavel
Mikhaylovich; KAPLAN, Moiseye Yakovlevich; PINSKIY,
Grigoriy Borisovich; ZHERVE, G.K., nauchn. red.;
ZARITSKIY, Ya.V., red.

[Design of hydrogenerators] Proektirovaniye gidrogenera-
torov. [By] V.V.Dombrovskii i dr. Moskva, Energiia.
Pt.1. 1965. 257 p. (MIRA 18:3)